

European Compressor Couplings and Clamps

- Sizes:** 3/8" to 1" (DN10 to DN25)
- Material:** Ductile Iron, Malleable Iron, Investment Cast Carbon Steel. Gold Chromate Plated
- Couplings:** Generally designed to interchange with DIN 3489:2001 couplings
- Clamps:** Generally designed to interchange with DIN 20039:1998 clamp
- Pressure:**
 Couplings: Maximum working pressure 150psi/10 Bar
 Claw Clamps: Maximum working pressure 360psi/25 Bar
 Non-ClawClamp: Maximum working pressure 232psi/16 Bar
- Threads:** BSP Pl. / BSPT in accordance with ISO 228



MALE ADAPTER	
PART NO.	SIZE
QDM38M	3/8"
QDM50M	1/2"
QDM75M	3/4"
QDM100M	1"



FEMALE ADAPTER	
PART NO.	SIZE
QDF38M	3/8"
QDF50M	1/2"
QDF75M	3/4"
QDF100M	1"



HOSE END	
PART NO.	SIZE
QDHE38M	3/8" (No Collar)
QDHE50M	1/2" (No Collar)
QDHE75M	3/4" (With Collar)
QDHE100M	1" (No Collar)



WASHERS FOR 2-LUG	
PART NO.	DESCRIPTION
EAWR4*	Black Natural Rubber
AWS6*	Neoprene

Temperature Range:
 -29°C (-20°F) to 71°C (160°F).

*Sold only in bags of 50.



SERIES TSC - TWO-BOLT SADDLE CLAMPS (MALLEABLE IRON)		
PART NO.	INCHES	HOSE O.D. RANGE (mm)
TSC25	5/8" - 15/16"	17 - 22
TSC31	15/16" - 1/8"	22 - 29
TSC34	1 1/16" - 1 1/4"	27 - 32
TSC37	1 1/4" - 1 7/16"	32 - 37
TSC1305	1 1/2" - 1 15/16"	39 - 49
TSC1306	1 29/32" - 2 3/8"	48 - 60
TSC1307	2 3/8" - 3 1/64"	60 - 76
TSC1308	3 1/32" - 3 11/16"	77 - 94
TSC1309	3 11/16" - 4 1/2"	94 - 115
WITH SAFETY CLAWS		
TSK34	1 1/8" - 1 1/4" (Investment Cast Steel)	28 - 32