

## High Pressure Couplings and Adapters



### 2"(DN50) COUPLER FOR SAFETY CLAMP

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPCG50SC	60 Bar	316 / 1.4401 / Z6CND17.11



### 2"(DN50) COUPLER FOR CRIMP FERRULE

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPCG50CF	60 Bar	316 / 1.4401 / Z6CND17.11

### 2"(DN50) COUPLER FOR WIRE WHIP

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPCG50W	60 Bar	316 / 1.4401 / Z6CND17.11



### 2" (DN50) COUPLER x BSP PL. FEMALE THREAD

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPCG50BSPF	60 Bar	316 / 1.4401 / Z6CND17.11



### 2" (DN50) ADAPTER WITH TAIL FOR SAFETY CLAMP

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPA50SC	60 Bar	316 / 1.4401 / Z6CND17.11

B



2" (DN50) ADAPTER WITH TAIL FOR CRIMP FERRULE		
MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPA50CF	60 Bar	316 / 1.4401 / Z6CND17.11

2" (DN50) ADAPTER WITH TAIL FOR WIRE WHIP		
MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPA50W	60 Bar	316 / 1.4401 / Z6CND17.11



2" (DN50) ADAPTER x BSP PL. FEMALE THREAD		
MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPA50BSPF	60 Bar	316 / 1.4401 / Z6CND17.11



2.5" (DN65) x 2" (DN50) BSP PL. FEMALE THREAD COUPLER		
MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPCG65BSPF	100 Bar	316 / 1.4401 / Z6CND17.11



2" (DN50) SAFETY CLAMP		
MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPSC50	60 Bar	316 / 1.4401 / Z6CND17.11



### 2" (DN50) HOLEDALL®, CRIMP FERRULE

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPH50CF	60 Bar	ASTM A106 / DIN 2448 / 1629 ST52.0



### 2" (DN50) x BSP PI. MALE THREAD HOLEDALL®, IX STEM

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPH50IXS	60 Bar	316L / 1.4404 / Z2CND17.12

Note: IX = Internal Expansion.



### 2" (DN50) HOLEDALL®, IX FERRULE (PLASTIC)

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPH50IXFP	60 Bar	Cast Nylon

Note: IX = Internal Expansion.



### 2" (DN50) HOLEDALL®, IX FERRULE (CARBON STEEL)

MODEL NO.	MAX. WORKING PRESSURE	MATERIAL
HPH50IXFC	60 Bar	ASTM A106 / DIN 2448 / 1629 ST52.0

Note: IX = Internal Expansion.