

Siliconschläuche und -schlauchleitungen mit Edelstahlwendel

SILICON DV 655/TB							
Innen Ø mm	Wand- stärke	Außen Ø mm	Max. Betriebsdruck in Bar (20°C)	Max. Platzdruck bei Bar (20°C)	Gewicht ±5% g/m	Vaku- um- beständigkeit	Mindestbiegeradius mm
6	6.5	19	21.1	63	44	-0.91	32
8	6.5	21	19.3	58	128	-0.912	42
9	6.5	22	18.6	56	170	-0.912	47
10	6.5	23	18.0	54	212	-0.912	52
11	6.5	24	17.4	52	254	-0.912	58
12	6.5	25	16.9	51	296	-0.912	63
13	6.5	26	16.4	49	338	-0.912	68
14	6.5	27	16.0	48	380	-0.912	74
15	6.5	28	15.5	47	422	-0.912	79
16	6.5	29	15.1	45	464	-0.912	85
17	6.5	30	14.8	44	506	-0.912	90
18	6.5	31	14.4	43	548	-0.912	96
19	6.5	32	14.1	42	590	-0.912	101
20	6.5	33	13.8	41	632	-0.912	107
22	6.5	35	13.2	40	716	-0.912	118
25	6.5	38	12.4	37	842	-0.912	136
26	6.5	39	12.2	37	884	-0.912	142
27	6.5	40	12.0	36	926	-0.912	148
28	6.5	41	11.7	35	968	-0.912	153
28.6	6.5	41.6	11.6	35	993.2	-0.912	157
30	6.5	43	11.3	34	1052	-0.912	166
32	6.5	45	10.9	33	1136	-0.912	178
34	6.5	47	10.6	32	1220	-0.912	190
35	6.5	48	10.4	31	1262	-0.912	196
38	7	52	9.9	30	1388	-0.912	215
39	7	53	9.7	29	1430	-0.912	222
40	7	54	9.6	29	1472	-0.912	228
42	7	56	9.3	28	1556	-0.912	241
43	7	57	9.1	27	1598	-0.912	248
44	7	58	9.0	27	1640	-0.912	254
45	7	59	8.9	27	1682	-0.912	261
46	7	60	8.7	26	1724	-0.912	268
47	7	61	8.6	26	176	-0.912	274
48	7	62	8.5	25	1808	-0.912	281
50	7	64	8.2	25	1892	-0.912	295
51	7	65	8.1	24	1934	-0.912	302
52	7	66	8.0	24	1676	-0.912	308
53	7	67	7.9	24	2018	-0.912	315
54	7	68	7.8	23	2060	-0.912	322
55	7	69	7.7	23	2102	-0.912	329
56	7	70	7.5	23	2144	-0.912	336
57	7	71	7.4	22	2186	-0.912	344
59	7	73	7.2	22	2270	-0.912	358
60	7	74	7.1	21	2312	-0.912	365
62	7	76	6.9	21	2396	-0.912	380
63	7	77	6.8	20	2438	-0.912	387
63.5	7	77.5	6.8	20	2459	-0.912	391
65	7	79	6.6	20	2522	-0.912	402
69	7	83	6.3	19	2690	-0.912	432
70	7	84	6.2	19	2732	-0.912	440
73	7	87	5.9	18	2858	-0.912	463
75	7	89	5.8	17	2942	-0.912	479
76	7	90	5.7	17	2984	-0.912	486
80	7	94	5.4	16	3152	-0.912	518
83	7	97	5.2	15	3278	-0.912	543
85	7	99	5.0	15	3362	-0.912	559
87	7	101	4.9	15	3446	-0.912	576
90	7	104	4.7	14	3572	-0.912	601
95	7	109	4.3	13	3782	-0.912	644
100	7	114	4.0	12	3992	-0.912	687
101	7	115	4.0	12	4034	-0.912	696
102	7	116	3.9	12		-0.912	705