

GT-Series Snap-Tite "23" Interchange

- Compact profile is ideal for installation in tight spaces or applications that require a reduction in coupling weight
- Couplers have a high concentration of locking balls to reduce incidents of brinelling during operation
- Valve design minimises spillage upon disconnection and air inclusion during connection
- Specially designed for utility vehicles and related applications requiring a compact rugged coupling
- Highly durable materials and corrosion resistant plating improves performance



PERFORMANCE SPECIFICATIONS	OPERATING bar (psi)	BURST bar (psi)	FLOW RATE ΔP=1.5 bar	LOCKING MECHANISM
3/8"	207 (3,000)	607 (8,800)	34 LPM (9 GPM)	Threaded

'GT' SERIES INTERCHANGE	SNAP-TITE	FASTER	-	-
3/8"	23-Series	Series 'IPP'	-	-



(Female Thread)

GT-SERIES SNAP-TITE '23' INTERCHANGE (COUPLER)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
3GTF3	3/8"	3/8"-18 NPTF	Steel



(Female Thread)

GT-SERIES SNAP-TITE '23' INTERCHANGE (COUPLER WITH SLEEVE BANDS)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
3GTF3-TG	3/8"	3/8"-18 NPTF	Steel



(Female Thread)

GT-SERIES SNAP-TITE '23' INTERCHANGE (NIPPLE)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
GT3F3	3/8"	3/8"-18 NPTF	Steel