

## J-Series Truflate Automotive Interchange


- The J-Series is fully interchangeable with the Parker Truflate series, sizes 1/4" to 1/2"
- 1/4" J-Series couplers are made of brass with a steel sleeve and are available in all brass or brass flanged sleeve configurations
- 3/8" and 1/2" couplers are constructed of plated steel to maximise performance and durability
- Couplers have a sleeve-guard 'Lip' to reduce the risk of accidental disconnection while in service



PERFORMANCE SPECIFICATIONS	OPERATING bar (psi)	BURST bar (psi)	FLOW ΔP=0.4 bar (6.9 bar inlet)	LOCKING MECHANISM
1/4"	34 (500)	233 (3,380)	37 CFM	6 Balls
3/8"	34 (500)	276 (4,000)	70 CFM	6 Balls
1/2"	34 (500)	414 (6,000)	150 CFM	6 Balls

'J' SERIES INTERCHANGE	PARKER	TOMCO	COILHOSE	RECTUS
1/4"	10-Series	A2100	Type '16'	55KM
3/8"	10-Series	PT400	Type '59'	-
1/2"	10-Series	-	-	-

### J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (MANUAL COUPLER)



(Female Thread)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2JF1-B	1/4"	1/8"-27 NPTF	brass
2JF2-B	1/4"	1/4"-18 NPTF	brass
2JBF2-B	1/4"	G1/4" BSPP	brass
2JF3-B	1/4"	3/8"-18 NPTF	brass
3JF2	3/8"	1/4"-18 NPTF	steel
3JF3	3/8"	3/8"-18 NPTF	steel
3JBF3	3/8"	G3/8" BSPP	steel
3JF4	3/8"	1/2"-14 NPTF	steel
4FF3	1/2"	3/8"-18 NPTF	steel
4FF4	1/2"	1/2"-14 NPTF	steel
4FBF4	1/2"	G1/2" BSPP	steel
4FF6	1/2"	3/4"-14 NPTF	steel

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (NIPPLE)



(Female Thread)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
J2F1	1/4"	1/8"-27 NPTF	steel
J2F2	1/4"	1/4"-18 NPTF	steel
J2F2-B	1/4"	1/4"-18 NPTF	brass
J2BF2	1/4"	G1/4" BSPP	steel
J2F3	1/4"	3/8"-18 NPTF	steel
J3F2	3/8"	1/4"-18 NPTF	steel
J3F3	3/8"	3/8"-18 NPTF	steel
J3BF3	3/8"	G3/8" BSPP	steel
J3F4	3/8"	1/2"-14 NPTF	steel
J4F3	1/2"	3/8"-18 NPTF	steel
J4F4	1/2"	1/2"-14 NPTF	steel
J4BF4	1/2"	G1/2" BSPP	steel
J4F6	1/2"	3/4"-14 NPTF	steel

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (MANUAL COUPLER)



(Male Thread)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2JM1-B	1/4"	1/8"-27 NPTF	brass
2JM2-B	1/4"	1/4"-18 NPTF	brass
2JM3-B	1/4"	3/8"-18 NPTF	brass
3JM2	3/8"	1/4"-18 NPTF	steel
3JM3	3/8"	3/8"-18 NPTF	steel
3JM4	3/8"	1/2"-14 NPTF	steel
4FM3	1/2"	3/8"-18 NPTF	steel
4FM4	1/2"	1/2"-14 NPTF	steel
4FM6	1/2"	3/4"-14 NPTF	steel

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (NIPPLE)



(Male Thread)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
J2M1	1/4"	1/8"-27 NPTF	steel
J2M2	1/4"	1/4"-18 NPTF	steel
J2M2-B	1/4"	1/4"-18 NPTF	brass
J2M3	1/4"	3/8"-18 NPTF	steel
J3M2	3/8"	1/4"-18 NPTF	steel
J3M3	3/8"	3/8"-18 NPTF	steel
J3M4	3/8"	1/2"-14 NPTF	steel
J4M3	1/2"	3/8"-18 NPTF	steel
J4M4	1/2"	1/2"-14 NPTF	steel
J4M6	1/2"	3/4"-14 NPTF	steel

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (MANUAL COUPLER)



(Standard & Push-Loc Hose Barb)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
2JS2-B	1/4"	1/4" Hose Barb	brass
2JB2-B	1/4"	1/4" Push-Loc	brass
2JS2.5-B	1/4"	5/16" Hose Barb	brass
2JS3-B	1/4"	3/8" Hose Barb	brass
2JB3-B	1/4"	3/8" Push-Loc	brass
3JS2	3/8"	1/4" Hose Barb	steel
3JS3	3/8"	3/8" Hose Barb	steel
3JB3	3/8"	3/8" Push-Loc	steel
3JS4	3/8"	1/2" Hose Barb	steel
4FS3	1/2"	3/8" Hose Barb	steel
4FS4	1/2"	1/2" Hose Barb	steel
4FB4	1/2"	1/2" Push-Loc	steel
4FS6	1/2"	3/4" Hose Barb	steel

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (NIPPLE)



(Standard & Push-Loc Hose Barb)

PART NO.	BODY SIZE	THREAD SIZE	BODY MATERIAL
J2S2	1/4"	1/4" Hose Barb	steel
J2B2	1/4"	1/4" Push-Loc	steel
J2S2.5	1/4"	5/16" Hose Barb	steel
J2S3	1/4"	3/8" Hose Barb	steel
J2B3	1/4"	3/8" Push-Loc	steel
J3S2	3/8"	1/4" Hose Barb	steel
J3S3	3/8"	3/8" Hose Barb	steel
J3B3	3/8"	3/8" Push-Loc	steel
J3S4	3/8"	1/2" Hose Barb	steel
J4S3	1/2"	3/8" Hose Barb	steel
J4S4	1/2"	1/2" Hose Barb	steel
J4B4	1/2"	1/2" Push-Loc	steel
J4S6	1/2"	3/4" Hose Barb	steel

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (MANUAL COUPLER)



(Reusable Barb)

PART NO.	BODY SIZE	BARB CONFIGURATION	BODY MATERIAL
2JE2-B	1/4"	1/4" ID X 3/8" OD	brass
2JH2-B	1/4"	1/4" ID X 5/8" OD	brass
2JK3-B	1/4"	3/8" ID X 11/16" OD	brass
2JL3-B	1/4"	3/8" ID X 3/4" OD	brass

## J-SERIES TRUFLATE AUTOMOTIVE INTERCHANGE (NIPPLE)



(Reusable Barb)

PART NO.	BODY SIZE	BARB CONFIGURATION	BODY MATERIAL
J2E2	1/4"	1/4" ID X 3/8" OD	steel
J2H2	1/4"	1/4" ID X 5/8" OD	steel
J2K3	1/4"	3/8" ID X 11/16" OD	steel
J2L3	1/4"	3/8" ID X 3/4" OD	steel