

Polypropylene Nozzle Valve

Sizes: 1" to 2"

Materials: Glass filled Polypropylene
Stainless Steel Handle, Spring & Pin



POLYPROPYLENE VALVES			
PART NO.	DESCRIPTION	PIPE SIZE	OPENING THRU BALL
VA-150	Bolted Valve - Full Port with Angle Hose End	1 1/2"	1 1/2"
VA-200/150	Bolted Valve - Standard Port with Angle Hose End	2 x 1 1/2"	1 1/2"
VA-200	Bolted Valve - Standard Port with Angle Hose End	2"	1 1/2"
All Stainless Bolts			



POLYPROPYLENE VALVES			
PART NO.	DESCRIPTION	PIPE SIZE	OPENING THRU BALL
VA-200-FP	Bolted Valve - Full Port with Angle Hose End	2"	2 1/16"
All Stainless Bolts			



POLYPROPYLENE VALVES			
PART NO.	DESCRIPTION	PIPE SIZE	OPENING THRU BALL
VA-100	Bolted Valve - Standard Port with Angle Hose End	1"	1 1/2"
All Stainless Bolts			



POLYPROPYLENE VALVES			
PART NO.	DESCRIPTION	PIPE SIZE	OPENING THRU BALL
UVA-100-FP	Single Union Poly Valve with Angle Hose End	1"	1"
All Stainless Bolts			



POLYPROPYLENE VALVES			
PART NO.	DESCRIPTION	PIPE SIZE	
VN-100	Poly Nozzle Valve	1"	
VN-10200	Repair Kit	-	

- Teflon® pin bushing
- Viton® rubber parts
- Resists corrosion
- Padlock capability
- 40 GPM
- Lightweight hose end valve
- Angled end flange with 8" fill spout

Trigger Nozzles – MK2

- Sizes:** Standard 1" BSP Pl. inlet
- Materials:** Aluminium body
Nitrile Seals
- Pressure:** Maximum working pressure 60 psi / 4 bar
- Details:**
- Ideal for Diesel fuel
 - For gravity or pumped use



TRIGGER NOZZLE MK 2	
PART NO.	DESCRIPTION
DATN	Basic
DATN/MS	Male Swivel Tail
DATNC/MS	With Trigger Catch
DATN/FS	With Female Swivel Tail
DATNC/FS	With Trigger Catch

Automatic

- Sizes:** Available in 3/4" BSP Pl. Female
- Materials:** Aluminium
- Pressure:** 30 psi / 2 bar minimum working pressure
- Details:**
- For Diesel dispensing
- Low flow shut down
 - Robust, quality construction
 - Simple lever catch
 - Automatic flow shut-off



AUTOMATIC NOZZLE	
PART NO.	DESCRIPTION
M3700	Fuel dispensing nozzle