

Washdown Guns

- Sizes:** 1/2" BSP Female
- Material:** Internals of Brass and Stainless Steel and possess hard wearing, scuff resistant blue rubber cover
- Pressure:** Maximum working pressure 24 bar / 350 psi
- Temperature:** Maximum working temperature 50°C / 122°F
- Delivery Rate:** 25L/min at 5 bar



WATER WASHDOWN GUN

PART NO.

DWG050

Various colours available.



BRASS TAILS NPT THREAD

PART NO.	SIZE
BN44	1/2" Thread x 1/2" Hosetail
BN64	1/2" Thread x 3/4" Hosetail

SPARE PARTS FOR DWG050

PART NO.	DESCRIPTION
DWGRS	Protective Rubber Sleeve
DWGN	Nozzle
DWGVB	Valve Colt (Gaskets)
DWGH	Rubber Handle
DWGS	Spring





INSULATED WATER NOZZLES

PART NO.

SN75

- Heavy duty brass valve and adjusting nut
- Hold open clip locks any spray pattern
- Chrome plated all zinc body
- Industrial strength nylon handle
- Rubber head guard
- Hot water up to 82°C (180°F)
- Threaded Female GHT supplied with Female NPT adapter



PISTOL-GRIP WATER NOZZLES

PART NO.

CSN75

- Heavy duty all zinc metalised body
- Clip locks any spray pattern
- Easy squeeze on/off lever
- All brass valve stem and adjusting nut
- Stainless Steel spring with lifetime pack
- Threaded Female GHT supplied with female NPT adapter



SOLID BRASS FULL SIZE NOZZLE

PART NO.

BTN75

- Thread 3/4" BSP female



MALE GHT x FEMALE NPT - TO SUIT ABOVE NOZZLES

PART NO.	MALE x FEMALE
BA794	GHT x 1/2"
BA796	GHT x 3/4"
FM1076	GHT x 1"